



**SHERWIN
WILLIAMS.**

103.25

PROCLASSIC[®]

Interior Waterbased Acrylic-Alkyd

Satin

B33-850 Series

As of 12/01/2012, Complies with:			
OTC	Yes	LEED [®] 09 CI	Yes
SCAQMD	Yes	LEED [®] 09 NC	Yes
CARB	Yes	LEED [®] 09 CS	Yes
CARB SCM 2007	Yes	LEED [®] H	Yes
MPI #	No	NGBS	Yes

CHARACTERISTICS

ProClassic Interior Waterbased Acrylic -Alkyd Satin is our finest quality high performance product, with superior flow and leveling characteristics for a smooth and durable finish.

Project Uses

- all trim areas and molding
- cabinets/doors/windows
- kitchens/baths
- laundry rooms
- high traffic areas

Substrates

- drywall/plaster
- paneling/wood
- metal
- concrete/masonry

Color: Most colors
To optimize hide and color development, always use the recommended P-Shade primer

Coverage: 350 - 400 sq ft/gal
@ 4 mils wet; 1.6 mils dry

Drying Time, @ 77°F, 50% RH:
Tack free: 20 - 40 minutes
Touch/hard: 1-2 hours
Recoat: 3-4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Finish:
24 hours 27-37 units @ 60°
30 days 20-30 units @ 60°

Flash Point: N/A

Tinting with CCE:

Base	oz/gal	Strength
Extra White	0-5	125%

Vehicle Type: Acrylic-Alkyd Hybrid
B33W00851

VOC (less exempt solvents):
<50 g/L; <0.42 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 38 ± 2%

Weight Solids: 53 ± 2%

Weight per Gallon: 10.8 lb

SPECIFICATIONS

Block

- 1 ct. Loxon Block Surfacer
- 2 cts. ProClassic Interior Waterbased Acrylic-Alkyd

Drywall

- 1 ct. Premium Wall & Wood Primer
- 2 cts. ProClassic Interior Waterbased Acrylic-Alkyd

Masonry

- 1 ct. Loxon Concrete & Masonry Primer
- 2 cts. ProClassic Interior Waterbased Acrylic-Alkyd

Plaster

- 1 ct. Premium Wall & Wood Primer
- 2 cts. ProClassic Interior Waterbased Acrylic-Alkyd

Wood

- 1 ct. Premium Wall & Wood Primer
- 2 cts. ProClassic Interior Waterbased Acrylic-Alkyd

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer.

Drywall

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.



PROCLASSIC®

Interior Waterbased Acrylic-Alkyd Satin B33-850 Series

<u>SURFACE PREPARATION</u>	<u>APPLICATION</u>	<u>CAUTIONS</u>
<p>Plaster Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p> <p>Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p>Caulking Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.</p>	<p>Apply at temperatures above 50°F. No reduction necessary</p> <p>Brush Use a nylon/polyester brush. Do not use a China bristle brush.</p> <p>Roller Use a 1/4" - 3/4" nap Soft Woven cover</p> <p>Spray—Airless Pressure..... 2000 psi Tip (fine finish)..... .010"-.014" (A fine finish tip is the preferred method of spray application due to the characteristics of this product. You can spray with tips from .013" to .017"; however, you should test the application on the particular item being painted.)</p> <p><u>CLEANUP INFORMATION</u> Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.</p>	<p>Non-photochemically reactive. For exterior use on doors, trim, and other small areas of wood or metal. Do not use on the main body of exterior structures.</p> <p>CAUTIONS Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p> <p>HOTW 03/25/2013 B33W00851 10 49</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>